

Solids Suspension in Tall Tanks

Richard F. COPE, Madan SOMASI, Kishore K. KAR

The Dow Chemical Company
Midland, Michigan 48674

Abstract

Uniformly suspending slurry solids in process vessels (reactors, crystallizers, storage tanks, etc.) of various sizes and shapes is a significant challenge in the chemical industry. This may be a bigger issue in manufacturing processes using glass-lined vessels, such as suspension polymerization, where large capacity vessels are disproportionately tall due to size constraints on the vessel manufacturer's glass-firing furnace. While tall tanks offer the enticement of higher capacity with a lesser foot print, uniformly suspending solids within such vessels is still a very daunting challenge.

The extensive work in solids-liquid systems is well represented in Paul et al. (2004) and such recent studies as (Brown et al., 2007; Himmelsbach et al., 2007; Spogis and Nunhez, 2007; Khazam and Kresta, 2006; Dittl and Rieger, 2006; Bao et al., 2005). These works involve experimentation and/or computer modelling to examine a variety of floating or settling solids, and traditional and/or new impeller types operating at various conditions of agitation speed and flow direction. The research described in this document seeks to understand the performance of a multi-tier agitation system consisting of either axial flow hydrofoils or mixed flow pitched blade turbines in uniformly suspending a specific settling solid in water throughout a "tall" laboratory vessel.

This study determined how the solids distribution changes as a function of solids loading (10, 20, 30, and 40 wt%), mixing rate (100, 150, 200, 250 RPM), and impeller type (pitched blade turbine (PBT) or wide-blade hydrofoil (Lightnin A320 or A340)). All work was conducted in a 17.5 in. ID Plexiglas® tank, with a slurry height of 35 in. At fixed operating conditions, the solids concentrations were obtained at four different axial tank locations. The results indicate that both impeller types produced a uniform solids suspension when the rotation rate produced an energy input of at least 6 HP/1000 gallons for the hydrofoils, and 7 HP/1000 gallons for the PBTs. Significantly higher energy or rotation rates improved the solids distribution only slightly because, at some point, flow within the vessel appeared to become choked.

keywords: solids, suspension, hydrofoil, PBT

Contact Author's Information:

Name: Richard F. Cope
Address: Building 1776
Phone number: 989-638-7923
e-mail address: coperf@dow.com

Presenting Author's Information:

As above: Yes

Please specify whether you wish to be considered for an oral ☒ or poster ☐ presentation. **Oral**

Do you anticipate submitting a full paper to the special Mixing issue of the Canadian Journal of Chemical Engineering? **Yes**